

MiniGlaze 2

*Fiber Muffle for Increased Performance
Adjustable Temperature Rate
Automatic Temperature Control
Easy-To-Read Temperature Indicator
Low Energy Consumption
Portable and Lightweight
Two-Year Warranty*

A Compact Porcelain Furnace For Staining and Glazing



The NeyTech MiniGlaze 2 is an economical, compact porcelain furnace...for dental office or laboratory air-fire staining and glazing. Final chairside esthetics are easily achieved with this portable, lightweight unit. The MiniGlaze 2 is essential for the dentist or technician who takes pride in offering customized service.

The MiniGlaze 2 is simple to operate. The user simply selects the desired temperature and the MiniGlaze 2 automatically controls muffle temperature and temperature rise rate. This assures precise staining and glazing conditions. The precise, dual-scale pyrometer displays actual muffle temperature in Fahrenheit and Centigrade. The Clear Vue Door™ permits observation of staining, glazing and calibration operations. The exterior cabinet is constructed of durable aluminum and steel with a baked-on enamel finish.

The MiniGlaze 2 can be set for audible tone or indicating light to signal when the set temperature has been reached. A large, easy-to-read temperature control dial allows the operator to set the muffle temperature from 200°C (392°F) to 1093° (2000°F). Temperature rise rate can be adjusted to a maximum 85°C (150°F) per minute or at a minimum 25°C (45°F) per minute.

For better dentistry

DENTSPLY
PROSTHETICS

CERAMCO

DENTSPLY International, Inc.
570 West College Avenue
York, PA 17405-0872, 717-699-4190
www.ceramco.com or www.dentsply.com

800353 Rev. 02/08

MiniGlaze

Specifications

Dimensions:	Cabinet	15.2 cm x 16.5 cm x 28.9 cm 16" w x 6-1/2" d x 11-3/8" h Overall Width with shelf, 20.4 cm/8"
	Chamber	6.4 cm x 8.9 cm x 4.5 cm 2-1/2" w x 3-1/2" d x 1-3/4" h
Weight		3.2 kg (7 lbs.)
Operating Voltages		120V (100V-132V), 50-60 Hz 220V (200V-250V), 50-60 Hz
Power		750 Watts
Temperature Accuracy		+ 10°C @ 1000°C + 18°F @ 1832°F
Heat Rise Rate		25°C - 85°C/min. 45°F - 150°F/min.
Operating Temperature Range		200°C - 1093°C 392°F - 2000°F

Suggested Accessories

Tongs

For safe handling of porcelain trays and furnace doors.
Heavy duty stainless steel, available in two sizes:
25.4 cm (10") and 30.5 cm (12") length.

Porcelain Firing Trays

For holding or carrying restoration. Available in various sizes and styles. All trays are made of high temperature refractory material and are thermal shock resistant.

Calibration Kit

Provides accurate temperature indication without damage to the muffle. Contains 100 pieces of pure silver.

Warranty

One-year limited warranty from date of sale on workmanship and material.